(12) United States Patent **Dooley**

(10) Patent No.:

US 6,257,566 B1

(45) Date of Patent:

Jul. 10, 2001

(54)	MULTIPI	LE SIGNATURE PEEDER SYSTEM
(75)	Inventor:	Rouald E. Dooley. Mattoon, IL (US)
(73)	Assignee:	R. R. Donnelley & Sons Co., Chicago, IL (US)
(*)	Notice:	Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.
(21) Appl. No.: 09/073,487		
(22)	Filed:	May 6, 1998
(51)	Int. Cl.7	B65H 39/043
		270/52.18: 270/52.18:
10-,		70/52-29; 270/52.14; 270/52.16; 271/3.03
(58) Field of Search 271/3.03, 3.12		
271/3.01, 9.01, 9.02, 9.13; 270/1.01, 1.02		
		52.14, 52.16, 52.18, 52.29, 58.29, 58.23,
		58.26, 52.22; 221/10
(56)		References Cited
U.S. PATENT DOCUMENTS		
3.841,622 10/1974 Swanson .		
4.208,666 6/1980 Paranjpe .		
4.801.036 * 1/1989 Rathert		
4.903,600 * 2/1990 Long		
5.088.711 * 2/1992 Newsome		

5.280.895 * 1/1994 Meier ... 5.458.323 * 10/1995 Magee et al. ..

5.727.781 * 3/1998 Muller 270/58.29 X * cited by examiner Primary Examiner-Christopher P. Ellis Assistant Examiner-Patrick Mackey (74) Attorney, Agent, or Firm-Marshall. O'Toole.

ABSTRACT

Gerstein, Murray & Borun

A binding line having increased capacity and increased flexibility to deliver customized or personalized signatures to the gathering conveyor in order to customize or personalizes the content of a book to appeal to targeted demographic groups or individuals. The binding line includes a gathering conveyor, a plurality of packer boxes positioned along the gathering conveyor, each of the packer boxes being adapted to deliver a distinct signature to the conveyor, and a feeder system operatively associated with at least one of the packer boxes. The feeder system includes a feed conveyor and a plurality of feeder boxes, each of the feeder boxes being adapted to deliver a selected signature to the associated packer box. A primary controller is provided for activating a selected set of the packer boxes, thereby delivering a set of signatures to the gathering conveyor. The primary controller further activates a selected one of the feeder boxes, thereby delivering a selected signature from the feeder system to the selected packer box. Preferably, a printer is provided for imprinting a customized or personalized message on each of the signatures selected from the feeder system prior to delivery to the associated packer box.

15 Claims, 3 Drawing Sheets

